

EC210 二层钢丝编织软管

符合 EN853 2SN



Winner by Danfoss **EC210-04**

6.4 MM (0.25 IN)
DN6

SAE 100R2 • EN 853 2SN
MSHA IC-84/41 • DNV

400 BAR (5800 PSI)

-40°C to +100°C
-40°F to +212°F

1A 2PC

结构: 合成橡胶内层，二层钢丝编织增强层，黑色合成橡胶外层。

PART #	SIZE DIMENSIONS				PRESSURE				BEND		WEIGHT	
	Hose I.D.		Hose O.D. (nominal)		Working Pressure	Min. Burst Pressure		Min. Bend Radius		Weight		
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
EC210-04	6.4	0.25	15.7	0.62	400	5,800	1,600	23,200	100	3.94	0.38	0.26
EC210-05	7.9	0.31	17.3	0.68	350	5,100	1,400	20,400	115	4.53	0.43	0.29
EC210-06	9.5	0.37	19.7	0.78	330	4,800	1,320	19,200	130	5.12	0.54	0.36
EC210-08	12.7	0.50	23.0	0.91	275	4,000	1,100	16,000	180	7.09	0.64	0.43
EC210-10	15.9	0.63	26.2	1.03	250	3,650	1,000	14,600	200	7.87	0.75	0.50
EC210-12	19.0	0.75	30.1	1.19	215	3,125	860	12,500	240	9.45	0.93	0.62
EC210-16	25.4	1.00	38.9	1.53	165	2,400	660	9,600	300	11.81	1.29	0.87
EC210-20	31.8	1.25	49.5	1.95	125	1,800	500	7,200	420	16.54	1.89	1.27
EC210-24	38.1	1.50	55.9	2.20	90	1,300	360	5,200	500	19.69	2.10	1.41
EC210-32	50.8	2.00	68.6	2.70	80	1,150	320	4,600	630	24.80	2.76	1.85
EC210-40	63.5	2.50	81.0	3.19	69	1,000	276	4,000	760	29.92	3.80	2.55
EC210-48	76.2	3.00	93.0	3.66	50	725	200	2,900	900	35.43	4.03	2.71

工作温度范围: -40°C 到 +100°C (-40°F 到 +212°F)

匹配接头: TTC 系列 | Winner 分体式接头

应用:

石油基或水基液压油的液压系统，适用各种工业行业。如有其它特殊应用需求，请联系 Danfoss。

行业认证:

MSHA

DNV